

TEKA LU averaging temperature transmitter is designed for automatic ventilating systems to measure large air duct temperatures. Thanks to the special mechanical construction the transmitter is able to detect temperature throughout its entire length. Information of the transmitter can be used to control other device in the HVAC system.

Temperature is measured by four Pt1000 sensor elements. The sensor elements resistance information is converted into a 0...10 V signal. The temperature range can be chosen at the commissioning.

TEKA LU settings can be changed by using the ML-SER tool. One point field calibration of the transmitter can be executed and the temperature output can be changed to the controller function.

TEKA LU transmitter can be equipped with a 3.5-digit liquid crystal display option TE-N V2. The display resolution is 0.1 °C.

Housing is made of heat resistant plastics. The bayonet cover and the terminal blocks tilted to 45° make an easy installation. Transmitter is mounted to the duct by means of an adjustable duct connection flange and springs for the optimal temperature measurement. 6 m length TEKALP is available on special request.

#### Range selection

0...+50 °C		*0...+100 °C		-50...+50 °C		-50...+150 °C	
S1	S2	S1	S2	S1	S2	S1	S2
●	●	●	●	●	●	●	●

\* = factory setting

#### Output signal

0...+50	0...+100	-50...+50	-50...+150	Signal
0 °C	0 °C	-50 °C	-50 °C	0 V
25 °C	50 °C	0 °C	50 °C	5 V
50 °C	100 °C	50 °C	150 °C	10 V



#### Technical data:

supply voltage	24 Vac/dc < 1 VA (22...30Vac/dc)
sensor	4 x Pt1000 EN 60751/B
output	0...10 Vdc < 2 mA (temperature / controller)
temperature range	selectable
duct mounting	Ø 10 mm hole and flange, 3 springs
measuring element	3 m
housing	plastics (< 120 °C)
protection class	IP54, cable entry or stem down
cable entry	M16
accuracy	± 0.5 °C (at 50 °C)
ambient temperature	0...+60 °C

#### Wiring:

1	supply 24 Vac/dc
2	0 V
3	output 0...10 Vdc (temperature / controller)

#### Ordering guide:

Model	Product number	Description
TEKA LU	1179130	averaging temperature transmitter
TE-N V2	1170250	display module (cover)
ML-SER	1139010	transmitter commissioning tool

All specifications are subject to change without notice



# TECHMARK

— Industriesteuerungen GmbH — <http://www.techmark.de> — e-mail: [info@techmark.de](mailto:info@techmark.de) —  
Kirschstrasse 20 • D-80999 München • Telefon (+49-89) 89.26.57-0 • Telefax (+49-89) 89.26.57-33

TEKA LL 2-wire averaging temperature transmitter is designed for automatic ventilating systems to measure large air duct temperatures. Thanks to the special mechanical construction the transmitter is able to detect temperature throughout its entire length. Information of the transmitter can be used to control other device in the HVAC system.

Temperature is measured by four Pt1000 sensor elements. The sensor elements resistance information is converted into a 4...20 mA signal. The temperature range can be chosen at the commissioning.

TEKA LL settings can be changed by using the ML-SER tool. One point field calibration of the transmitter can be executed and the temperature output can be changed to the controller function.

TEKA LL transmitter can be equipped with a 3.5-digit liquid crystal display option TE-N V2. The display resolution is 0.1 °C.

Housing is made of heat resistant plastics. The bayonet cover and the terminal blocks tilted to 45° make an easy installation. Transmitter is mounted to the duct by means of an adjustable duct connection flange and springs for the optimal temperature measurement. 6 m length option TEKALP6 is available on special request.

#### Range selection

0...+50 °C	*0...+100 °C	-50...+50 °C	-50...+150 °C
S1 S2	S1 S2	S1 S2	S1 S2
■ ●	■ ■	● ●	● ●

\* = factory setting

#### Output signal

0...+50	0...+100	-50...+50	-50...+150	Signal
0 °C	0 °C	-50 °C	-50 °C	4 mA
25 °C	50 °C	0 °C	50 °C	12 mA
50 °C	100 °C	50 °C	150 °C	20 mA



#### Technical data:

supply voltage	15...35 Vdc
sensor	4 x Pt1000 EN 60751/B
output	4...20 mA (temperature / controller)
temperature range	selectable
duct mounting	Ø 10 mm hole and flange, 3 springs
measuring element	3 m
housing	plastics (< 120 °C)
protection class	IP54, cable entry or stem down
cable entry	M16
accuracy	± 0.5 °C (at 25 °C)
ambient temperature	0...+60 °C
transmitter type	2-wire

#### Wiring:

- 1 +(-) temperature signal or controller 4...20 mA
- 2 - (+) temperature signal or controller 4...20 mA

NOTE: The electrical wiring is polarity free.

#### Ordering guide:

Model	Product number	Description
TEKA LL	1177130	averaging temperature transmitter
TE-N V2	1170250	display module (cover)
ML-SER	1139010	transmitter commissioning tool

All specifications are subject to change without notice



# TECHMARK

— Industriesteuerungen GmbH — <http://www.techmark.de> — e-mail: [info@techmark.de](mailto:info@techmark.de) —  
 Kirschstrasse 20 • D-80999 München • Telefon (+49-89) 89.26.57-0 • Telefax (+49-89) 89.26.57-33